

Mirror Glue 280 ml

Product Description

Permanently elastic single-component mirror adhesive. Excellent adhesion to metal, aluminum, glass, plastic, wood and concrete. It can be painted with all kinds of paints (including water-based paints).

Properties

Moisture resistant, solvent and isocyanate-free, no bubble formation, excellent UV resistance, environment friendly, resistant to chemicals, easy application.

Technical Information

Specific gravity: $1,56 \pm 0,03 \text{ g/cm}^3$
 Tack free time: > 15 min (25 °C and 50% R.H)
 Cure Rate(1 day): 2 mm (25 °C and 50% R.H)
 Tensile Strength: $\approx 1,80 \text{ Mpa}$
 Elongation at Break: > 250
 Shore Hardness: $55 \pm 5 \text{ Shore A}$

Application Details

Application Temperature: +5 °C to 35 °C
 Temperature Resistance: -40 °C to 90 °C
 Application surface must be clean, dry and free of dust, oil and grease.

Shelf Life

Store the product in a cool and dry place.
 The shelf life is 12 months at temperatures between +5 °C and +25 °C.

Caution

Avoid contact with skin and eyes. Use gloves before application. Keep out of freezing, direct sunlight and temperatures above 50 °C. Apply in well-ventilated areas. Do not breathe vapor. Do not smoke.

Health and Safety

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing, physical, ecological, and toxicological and other safety related data.




Code

Barcode

LZO

8605043408183

Logistics data

Barcode	8605043408183			Code
Cartridge length	23,3			LZO
Cartridge width	4,9			
Cartridge diameter	4,9			
Packaging	Dimensions	Number of boxes	Number of cartridge	Gross weight (Kgs)
Commercial packaging	25.2.x25.2x25	1	25	12,8
Transpot packing	25.2.x25.2x25	1	25	12,8
Pallet for storage	1200x800x2200	75	1875	960
Pallet for transport	1200x800x2200	75	1875	960